



R = 0.3以下

ロッドの表面は、0.8~1.6 μ mRy (0.2~0.4 μ mRa) のバフ仕上げ (SPBF) として下さい。

ダストシール呼び寸法				装着部寸法		
d	D	t	h	φd	φD	H
92	106	8	11	92	106	8 \pm 0.05
95	109			95	109	
100	114			100	114	
105	121	9	12	105	121	9 \pm 0.05
106	122			106	122	
108	125			108	125	
110	126			110	126	
112	128			112	128	
115	131			115	131	
118	134			118	134	
120	136	10	14	120	136	10 \pm 0.05
125	141			125	141	
130	146			130	146	
132	148			132	148	
135	155			135	155	
140	160			140	160	
145	165			145	165	
150	170	12	17	150	170	12 \pm 0.05
155	175			155	175	
160	180			160	180	
165	185			165	185	
170	190			170	190	
175	195			175	195	
180	205			16	22	
185	210	185	210			
190	215	190	215			
200	225	200	225			
210	235	210	235			
212	237	212	237			
220	245	220	245			
224	249	16	22	224	249	16 \pm 0.05
225	250			225	250	
230	255			230	255	
236	261			236	261	
240	265			240	265	
245	270			245	270	
250	275			250	275	
260	285	16	22	260	285	16 \pm 0.05
265	290			265	290	
280	310			280	310	
290	320			290	320	
300	330			300	330	